

## Tyre 13.0/65-18 (340/65-18) IMB160 Ascenso 16PR 144A8 TL (ž/ū)

|          |         |                                      |                    |
|----------|---------|--------------------------------------|--------------------|
| Delivery | 1-5 w/d | Category                             | Agricultural tyres |
| Warranty |         | Size                                 | 13.0/65-18         |
|          |         | Model                                | IMB160             |
|          |         | Ply                                  | 16                 |
|          |         | Load ind. (LI)                       | 144                |
|          |         | Speed ind. (SI)                      | A8                 |
|          |         | Maximum load per tire,<br>kg         | 2800               |
|          |         | Maximum speed, km/h                  | 40                 |
|          |         | Inflation pressure, atm              | 4.9                |
|          |         | Analog                               | 340/65-18          |
|          |         | Outer diameter (OD), mm              | 890                |
|          |         | Section Width (SW), mm               | 336                |
|          |         | Dynamic rolling<br>circumference, mm | 2662               |
|          |         | Static Loaded Radius, mm             | 408                |
|          |         | Recomend/permitted rim               | 11                 |
|          |         | Radial/ bias                         | Bias               |
|          |         | Origin                               | IN                 |
|          |         | TT / TL                              | TL                 |
|          |         | Komplektacija                        | TL                 |

### Description

All technical information about products in our website protekta.lt is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.