

**Tyre 15.5/80-24 (400/80-24) IM54 TVS 16PR 146A8/159A8 TL**

|                                   |                    |
|-----------------------------------|--------------------|
| Category                          | Agricultural tyres |
| Size                              | 15.5/80-24         |
| Model                             | IM54               |
| Ply                               | 16                 |
| Load ind. (LI)                    | 159 / 146          |
| Speed ind. (SI)                   | A8                 |
| Maximum load per tire, kg         | 4390 / 3015        |
| Maximum speed, km/h               | 40                 |
| Inflation pressure, atm           | 4                  |
| Analog                            | 400/80-24          |
| Outer diameter (OD), mm           | 1255               |
| Section Width (SW), mm            | 425                |
| Dynamic rolling circumference, mm | 3649               |
| Static Loaded Radius, mm          | 565                |
| Recomend/permitted rim            | 12                 |
| Radial/ bias                      | Bias               |
| Origin                            | IN                 |
| TT / TL                           | TL                 |
| Komplektacija                     | TL                 |

|             |           |
|-------------|-----------|
| Delivery    | ---       |
| Warranty    | 12 months |
| Description |           |

All technical information about products in our website protekta.lt is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.