

**Tyre 700/50-22.5 Flotation T422 Altura 16PR 174A8/162A8 TL**

|                                   |                    |
|-----------------------------------|--------------------|
| Category                          | Agricultural tyres |
| Size                              | 700/50-22.5        |
| Model                             | Flotation T422     |
| Ply                               | 16                 |
| Load ind. (LI)                    | 174 / 162          |
| Speed ind. (SI)                   | A8                 |
| Maximum load per tire, kg         | 6700 / 4750        |
| Maximum speed, km/h               | 40                 |
| Inflation pressure, atm           | 2.80               |
| Analogue                          |                    |
| Outer diameter (OD), mm           | 1238               |
| Section Width (SW), mm            | 700                |
| Dynamic rolling circumference, mm | 3650               |
| Static Loaded Radius, mm          | 550                |
| Recomend/permitted rim            | 24.00 DC           |
| Radial/ bias                      | Bias               |
| Origin                            | IN                 |
| TT / TL                           | TL                 |
| Komplektacija                     | TL                 |

|             |           |
|-------------|-----------|
| Delivery    | 1-5 w/d   |
| Warranty    | 12 months |
| Description |           |

All technical information about products in our website protekta.lt is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.