

**Tyre 520/85R38 (20.8R38) TA110 Petlas 155A8/152B TL**

|                                      |                    |
|--------------------------------------|--------------------|
| Category                             | Agricultural tyres |
| Size                                 | 520/85R38          |
| Model                                | TA110              |
| Ply                                  |                    |
| Load ind. (LI)                       | 155                |
| Speed ind. (SI)                      | A8                 |
| Maximum load per tire,<br>kg         | 3875               |
| Maximum speed, km/h                  | 40                 |
| Inflation pressure, atm              | 1.6                |
| Analogue                             | 20.8-38            |
| Outer diameter (OD), mm              | 1849               |
| Section Width (SW), mm               | 516                |
| Dynamic rolling<br>circumference, mm | 5529               |
| Static Loaded Radius, mm             | 828                |
| Recomend/permitted rim               | DW16L; DW18L       |
| Radial/ bias                         | Radial             |
| Origin                               | TR                 |
| TT / TL                              | TL                 |
| Komplektacija                        | TL                 |

|             |           |
|-------------|-----------|
| Delivery    | 1-5 w/d   |
| Warranty    | 60 months |
| Description |           |

All technical information about products in our website protekta.lt is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.