

**Tyre 385/65R22.5 NZ300 Petlas 20PR 164K TL M+S 3PMSF**

|                                      |                   |
|--------------------------------------|-------------------|
| Category                             | Truck & Bus tyres |
| Size                                 | 385/65R22.5       |
| Axle                                 | Trailer           |
| Season                               | Winter M+S        |
| Model                                | NZ300             |
| Ply                                  | 20                |
| Load ind. (LI)                       | 164               |
| Speed ind. (SI)                      | K                 |
| Maximum load per tire,<br>kg         | 5000              |
| Maximum speed, km/h                  | 110               |
| Inflation pressure, atm              | 9                 |
| Analogue                             |                   |
| Recomend/permitted rim               | 11.75             |
| Outer diameter (OD), mm              | 1                 |
| Section Width (SW), mm               |                   |
| Static Loaded Radius, mm             |                   |
| Dynamic rolling<br>circumference, mm |                   |
| TT / TL                              | TL                |
| Komplektacija                        | TL                |
| Rolling resistance                   | C                 |
| Wet grip                             | A                 |
| External noise, dB                   | 69                |

Delivery ---  
 Warranty ---

Description

All technical information about products in our website protekta.lt is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.