

**Tyre 385/55R22.5 GL252T Advance 20PR 160K TL M+S 3PMSF (tr.)**

|                                      |                   |
|--------------------------------------|-------------------|
| Category                             | Truck & Bus tyres |
| Size                                 | 385/55R22.5       |
| Axle                                 | Trailer           |
| Season                               | M+S               |
| Model                                | GL252T            |
| Ply                                  | 20                |
| Load ind. (LI)                       | 160               |
| Speed ind. (SI)                      | K                 |
| Maximum load per tire,<br>kg         | 4500              |
| Maximum speed, km/h                  | 110               |
| Inflation pressure, atm              | 9                 |
| Analogue                             |                   |
| Recomend/permitted rim               | 12.25             |
| Outer diameter (OD), mm              |                   |
| Section Width (SW), mm               |                   |
| Static Loaded Radius, mm             |                   |
| Dynamic rolling<br>circumference, mm |                   |
| TT / TL                              | TL                |
| Komplektacija                        | TL                |
| Rolling resistance                   | C                 |
| Wet grip                             | B                 |
| External noise, dB                   | 74                |

Delivery 1-5 w/d  
Warranty

Description

All technical information about products in our website protekta.lt is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.