

Tyre 13R22.5 M840EVO Bridgestone 158/156G TL M+S 3PMSF

| | | | |
|-------------|-----------|-----------------------------------|-------------------|
| Delivery | --- | Category | Truck & Bus tyres |
| Warranty | 12 months | Size | 13R22.5 |
| | | Axle | Stear |
| | | Season | Winter M+S |
| | | Model | M840EVO |
| | | Ply | |
| | | Load ind. (LI) | 158 / 156 |
| | | Speed ind. (SI) | G |
| | | Maximum load per tire, kg | 4250 / 4000 |
| | | Maximum speed, km/h | 90 |
| | | Inflation pressure, atm | 9.0 |
| | | Analog | |
| | | Recomend/permitted rim | 9.75 |
| | | Outer diameter (OD), mm | 1124 |
| | | Section Width (SW), mm | 320 |
| | | Static Loaded Radius, mm | |
| | | Dynamic rolling circumference, mm | |
| | | TT / TL | TL |
| | | Komplektacija | TL |
| | | Rolling resistance | D |
| | | Wet grip | B |
| | | External noise, dB | 72 |
| Description | | | |

All technical information about products in our website protekta.lt is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.